

TECHNICAL SPECIFICATION

ul. Sportowa, Cholierzyn




Area

<i>Terrein</i>	Entrance, gate / concierge, fence, maneuvering area for trucks, parking for passenger cars, development of the building space.
<i>Building</i>	A single-storey warehouse with office space. Clear height in the storage area 10 m (to the main beams).
<i>Exterior facade</i>	<ul style="list-style-type: none">• On the side of the docks: Walls of precast concrete elements with a height of:<ul style="list-style-type: none">> from -1.20 to 4.20 m at the docks> from 0.00 to 4.20 m at the "entrance" from level 0> from 0.00 to 0.30 m in other parts of the building, except for office premises• Sandwich panels in horizontal orientation with PIR filling, 10 cm thick• From the office side: Glass facade made of translucent and non-transparent colored glass. Aluminum window and door joinery, powder coated in RAL 5003 color.



Warehouse part

<i>Fire load</i>	Fire load up to 4000 MJ / m ²
<i>Column grid</i>	Column grid with a spacing of 22.5 m x 12 m and 22.5 x 24 m at the unloading docks
<i>The floor plate</i>	<ul style="list-style-type: none">• Uniformly distributed load of 5 T / m².• The floor slab - reinforced concrete, 17 cm thick (reinforced: dispersed reinforcement).• Surface hardening: dry mineral sprinkle, dust-free floor.• Surface flatness according to DIN 18202, table 3, line 3• Thermal insulation of ground beams, internal circumference.• Prefabricated reinforced concrete perimeter beams.• Jointless floor.• Prefabricated reinforced concrete dock sockets.
<i>Supporting structure</i>	<ul style="list-style-type: none">• Reinforced concrete columns, main steel beams.• Column grid 22.5 m x 12 m. Steel structure protected against corrosion.• In the front part of the docks, a reinforced concrete wall as a substructure for sectional gates.

<i>Sectional doors</i>	<ul style="list-style-type: none"> • Overhead sectional doors with electric drive: • 3 m x 3.2 m sectional docks with glazed section (number: 1/800m2) • 3.5 m x 4.2 m entrance gates from level 0 (number: 2 pcs - on both ends of the object with an area of 20,000 m²)
<i>Transshipment platforms</i>	<ul style="list-style-type: none"> • Electrical type Hörmann, Crawford or equivalent, static load capacity: 10,000 kg, dynamic load capacity 6,000 kg • Lip length 0.405 m, platform width 2.0 m. • Platform length 2.50 m, height 0.6 m, steel structure. • Dock height: 1.20 m • Dock seal: apron. Two rubber buffers with dimensions of 500x250x100mm at each loading platform. Trailer wheel guides for each loading platform - made of cubes.
<i>Roof</i>	The warehouse roof is flat, sheathing made of trapezoidal sheet metal, 0.63 mm thick, powder coated in a standard color. Roof insulation - hard mineral wool (when using a roof sheet with RE15 parameters) covered with a PVC membrane with a thickness of 1.2 mm. Design internal temperature in the storage area +15 ° C, at an outside temperature of -20 ° C.
<i>Roof drainage</i>	Underpressure roof drainage installation, emergency overflows in the walls of the attic.
<i>Lighting the warehouse area</i>	Access to daylight in the storage area - through smoke vents and skylights (lighting area in total 3% of the floor plan). NRO transparent polycarbonate filling. Starting the smoke exhaust from the sprinkler pump station.
<i>Door accessories</i>	Anti-panic mechanisms in all emergency exits. Door closers in fire-resistant doors and in the entrance door of the main office area.
 Office part	
<i>Offices and communication</i>	<ul style="list-style-type: none"> • The height of the offices is 3 m in the light. • GK internal walls and 120 mm thick block on steel system profiles with acoustic insulation made of mineral wool, painted with emulsion paint. • Finishing of floors: carpet in offices, ceramic tiles in social areas • Ceiling finishing: mineral system suspended ceiling on a grid, panels 60 cm x 60 cm in white. • Aluminum window frames, powder coated in RAL 5006. • Internal paneled doors (Porta, DRE or equivalent), adjustable wooden frame
<i>Technical rooms</i>	<ul style="list-style-type: none"> • Floor finish: faded concrete. • Finishing of walls: double painting with emulsion paint. • Doors: metal technical.
<i>Sanitary facilities</i>	<ul style="list-style-type: none"> • Internal plasterboard walls, approx. 120 mm thick, double-paneled (waterproof board) on steel system profiles with mineral wool acoustic insulation, painted twice with emulsion paint in white.

	<ul style="list-style-type: none"> • Floor finishing: 20 cm x 20 cm ceramic tiles in a standard color. • Wall finishing: white tiles up to 2m high, showers up to full height. • Ceiling finishing: mineral system suspended ceiling on a grid, panels 60 cm x 60 cm in white, waterproof. • Sanitary equipment: white ceramic sanitary ware (Koło, Cersanit). • Location of sanitary facilities and utensils - according to plan. • Sanitary equipment: hangers, towel dispensers, soap dispensers (Kludi, Oras, Merida).
--	--



Sanitary and mechanical installations

<i>Sanitary installations</i>	Sanitary sewerage in accordance with the requirements of engineering documents and regulations. Stormwater drainage in accordance with regulations. Water supply to the central office block provided with a meter and a branch to future office spaces. Compliant insulation of internal sewage and water pipes to prevent condensation and freezing.
<i>Fire protection</i>	ESFR sprinkler system (K240 heads) in the storage part, water supply for fire purposes from the fire tank. Internal hydrants and handheld firefighting equipment on the storage area in accordance with local regulations and requirements. External hydrants located on the premises of the facility. Permissible fire load on the warehouse: up to 4,000 MJ / m ² .
<i>Heating and ventilation</i>	Heating in the storage area - gas heaters. Design internal temperature in the storage area: 15 ° C with an outside temperature of - 20 ° C. In the office part, central heating is supplied by a gas boiler room or individual electric heaters. Calculated internal temperature in the office part: 20 degrees C, outside temperature - 20 ° C. Heating in sanitary facilities locally - electric heaters. Ventilation in the storage area: mechanical exhaust. Ventilation in the office and social part in accordance with the regulations.



Electrical Installations

<i>General</i>	<ul style="list-style-type: none"> • 800 kVA is expected as standard for a warehouse space of 30,000 m2. • Distribution of energy: main switchgear, facility switchgears. • Power supply: 230/400 V. • Electricity consumption billed according to the sub-calculator. One meter per warehouse space module as standard. • Power supply for the workplace: two clean sockets + two dirty sockets on an 8m2 purely office space. • Cleaning and general purpose sockets: one cleaning socket for every 20 m2 of room (corridors, sanitary facilities, lockers, cleaning room, technical room). • General purpose sockets in kitchenettes: 4 pcs. • In the warehouse part - a set of single-phase general-purpose sockets, 2 pcs + power socket (1 set per 3000 m2 of the hall) located next to the loading platform • Lightning protection - horizontal and vertical terminals
<i>Lighting</i>	<ul style="list-style-type: none"> • Fluorescent lamp lighting • 200 lux in the warehouse (before check-in), in sanitary rooms, corridors and staircases) • 150 lux in technical rooms • 500 lux in offices • Emergency lighting / signage for emergency exits at all LED emergency exits outside the building
<i>Telecommunication</i>	<p>Telecommunication sewage system (prepared for the installation of secondary sewage system) connected from the plot border to the building. The standard does not include low-voltage installations (CCTV, computer network, access control, etc.) - they can be valued at the customer's request.</p>